

## tesa® 64007

### Tamper Evident Carton Sealing Tape

tesa® 64007 is a tamper evident providing carton sealing tape.

With its characteristics tesa® 64007 helps to reduce pilferage during transport and storage of carton boxes.

tesa® 64007 is designed to avoid unnoticed opening and reclosure of carton boxes.

The tamper evident effect works in two steps:

- When tesa® 64007 is removed from the box, the product leaves the message "OPENED" in different languages on the carton.
- The tamper evident message "OPENED" remains clearly visible also after re-closure of the box.

The tamper evident effect may also be achieved through a complete carton fibre tear-out, which makes a re-closure impossible.

It can be used as a normal carton sealing tape on dispensers and machines with a brake.

Available Colours: yellow, blue

## Main Application

These characteristic makes tesa® 64007 especially suitable for the closure of cartons with valuable or confidential content as:

- Electronic products
- High value / branded clothing
- Tobacco products
- Documents

## Technical Data

|                    |                     |                       |          |
|--------------------|---------------------|-----------------------|----------|
| ▪ Backing material | BOPP                | ▪ Adhesion to steel   | 2.8 N/cm |
| ▪ Total thickness  | 62 µm               | ▪ Elongation at break | 150 %    |
| ▪ Type of adhesive | water-based acrylic | ▪ Tensile strength    | 42 N/cm  |

## Properties

|                         |     |                      |     |
|-------------------------|-----|----------------------|-----|
| ▪ Automatic application | yes | ▪ Manual application | yes |
|-------------------------|-----|----------------------|-----|

## Additional Information

It has to be pointed out that on very lower carton qualities the adhesion should be tested and that the tamper evident effect (legible message or fibre tear) cannot be guaranteed.

Value "adhesion/steel": no parameter of the specification, not measurable.

Please note "total thickness" for blue coloured tape is 66µm.

For latest information on this product please visit <http://l.tesa.com/?ip=64007>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.