borg& overström

03



# A re-imagined classic

Built from the strong foundations set by the b2 range, this product boasts additional features including a larger dispense area, integrated cup dispenser and the option of sparkling water.







Power requirements Hertz 50/Volts 220-240 Max power consumption Chilled & Ambient 100W

Chilled & Hot 550W
Chilled, Ambient & Hot 550W
Chilled, Ambient & Hot 550W
Chilled, Hot & Sparkling 640W
Chilled, Ambient & Sparkling 140W

Chilled temperature
Min 2°C/Max 11°C
Hot temperature
Max 92°C
Throughput litres per hour
Chilled 22/Hot 6

Dimensions
Floorstanding
Countertop
Dispense height

WxDxH 325x380x1065mm 325x380x475mm 210mm

## Key Features

- Touch panel button controls
- Auto lit dispense area
- Integrated cup dispenserShrouded faucet for hygenic protection
- Floorstanding or countertopAvailable in direct chill or reservoir
- Chilled, ambient, hot and sparkling

### Available accessories

- Waste Kit
- Leak Detection Kit
- Wall Bracket Set
- Cup Dispenser Blanking Plate
- Sparkling Refill (CO<sub>2</sub> E290)
- CO<sub>2</sub> Regulator with Gauge
   Sanitisation Kit

- Install Kit with Filter
- Waste Kit with Level Sensor
- Blue Tint Cups



#### Water options









Chilled

Ambient

Sparkling

#### Configuration





Countertop

Floorstanding

#### Recommended environment











Leisure

Number of users





6-10

11-2

#### b3 Models

Reservoir, Floorstanding, Chilled, Ambient—104910
Reservoir, Floorstanding, Chilled, Hot—104110
Reservoir, Countertop, Chilled, Ambient—104210
Reservoir, Countertop, Chilled, Hot—104310
Direct Chill, Floorstanding, Chilled, Ambient—104410
Direct Chill, Countertop, Chilled, Ambient—104510
Direct Chill, Countertop, Chilled, Hot—104615
Direct Chill, Floorstanding, Chilled, Ambient, Hot—104715
Direct Chill, Floorstanding, Chilled, Hot, Sparkling—104810

Direct Chill, Floorstanding, Chilled, Ambient, Sparkling—104815

#### Water system





Direct Chill

Reservoir

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone +44 (0)1362 695 006 Email sales@borgandoverstrom.com

borgandoverstrom.com

Distributed by

Ref: 838102 Version: 13012015