

## LEDsBIKE ACC101



### Robust and vibration resistant

Reliable hold even on rough terrain



### Easy to install

Quick-release design for fast mounting and removal



### 2-year OSRAM guarantee<sup>1)</sup>

Durable and lightweight – designed for long-term use



### Fast installation, reliable hold

Secure your LEDsBIKE lights with ease using the OSRAM mounting set. This set includes a Garmin-compatible bracket for the front light and a flexible rubber strap for the rear light. The universal handlebar mount fits diameters from 22.2 mm to 35 mm. Thanks to its quick-release design, installation and removal are effortless. Built for durability and stability, it withstands vibrations and prevents slipping even on rough terrain, while remaining lightweight for optimal performance. In addition, OSRAM offers a 2-year guarantee<sup>1)</sup>.

### Compatibility:

LEDsBIKE COMPACT 50/100

LEDsBIKE EXPLORER X 500/1000

LEDsBIKE MULTI BEAM X 1000

LEDsBIKE RACE REAR

LEDsBIKE COMPACT REAR

LEDsBIKE X REAR

Product datasheet

Technical data

Product information

|   |   |
|---|---|
| Application (Category and Product specific) | LED Bike Lights Mount   |
| Product legal advice 1                      | 1) For precise conditions refer to:<br>www.osram.com/am-guarantee |

General Product Information

|                        |              |
|------------------------|--------------|
| Global order reference | LEDBL ACC101 |
|------------------------|--------------|

Lifetime Data

|           |         |
|-----------|---------|
| Guarantee | 2 years |
|-----------|---------|

Additional product data

|                       |                                    |
|-----------------------|------------------------------------|
| Compatible handlebars | Ø 22.2 / 25.4 mm / 31.8 mm / 35 mm |
|-----------------------|------------------------------------|

Capabilities

|            |   |
|------------|---|
| Technology | - |
|------------|---|

Environmental & Regulatory Information

|   |               |
|---|---------------|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |               |
| Primary article identifier  | 4062172425964 |
| Declaration no. in SCIP database                                      | In work       |

Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|---|----------------------|--------------|
| 4062172425964 | LEDsBIKE ACC101     | Hanging Folding Box<br>1        | 62 mm x 46 mm x<br>94 mm                | 0.27 dm <sup>3</sup> | 47.00 g      |
| 4062172425971 | LEDsBIKE ACC101     | Shipping carton box<br>6        | 157 mm x 141 mm x<br>125 mm             | 2.77 dm <sup>3</sup> | 395.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File |
|------|
|------|

## Product datasheet



User instruction  
G15143063 UI LEDsBIKE ACC101 LEDBLACC101



User instruction  
GPRS\_Safety symbols instructions

### Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

### Legal advice

1) For precise conditions refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM