

Technical Datasheet

SAFETY MARKING “CAUTION! FORKLIFTS”



Art. No. 173404
 Colour yellow / W014
 EAN 4005546983493

Safety sign “caution! forklifts” according to DIN EN ISO 7010 / W014

Technical information

Foil		
floor tape	PVC-P foil	
execution	straight edges	
R-value	R9	according to DIN 51130
Dimensions		
thickness (transparent film)	0,70 mm	
	printed on the back	
adhesive base	modified solvent acrylic	
thickness adhesive layer	0,15 mm	
liner	white siliconized paper liner	
thickness liner	0,15 mm	
total thickness	1,00 mm	
diameter (mm)	430	
Adhesion properties		
Initial tack (cm)	< 6	according to PSTC-16
holding power (hr/25°C/cm ²)	> 24	according to ASTM 7
adhesion to steel (kg/25,4 mm ²)	> 6	according to PSTC 1
temperature resistance	-30° C to +70° C	1 h/° C
Packing		
packaging	1 pc. / PE bag / 5 bag in a carton	
weight	84 g/pc.	
Storage		
storage	in original packaging, store in following conditions	
storage conditions (approx.)	+18° C / 55 % humidity (RF)	
storage time	18 months	

DURABLE

Hunke & Jochheim GmbH & Co. KG
 Westfalenstraße 77-79
 D-58636 Iserlohn

Telefon +49 (0) 2371 / 662 – 0
 Telefax +49 (0) 2371 / 662 – 221
 Internet www.durable.de
 E-Mail durable@durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.



Processing temperatures	
minimum underground application temperature	+10° C
advised application temperature	+15° C to 25° C

Application	
areas of application	indoor

Resistance	
UV	good
weather	variable
mineral oils	good
vegetable oils	good
collant (containing compounds of esters and amines)	good
alkaline liquids (pH 7 - 9,5)	good
powerful alkaline liquids (pH 9,5 – 14)	variable
acids (pH 2 – 7)	good
powerful acids (pH 0 – 2)	variable
disinfectants	good
alcohol	good
chloride solutions	variable
solvents (aromatic aliphatic)	variable
halogenated solvents	variable
plasticizers like phatalates	slow degradation.
acetat and aldehyde	poor
ketones (acetone)	poor

Application Information	
floor conditions	The surface must be dry, firm, flat and closed and free of dirt, grease, dust, tar, wax and other dirt. In the case of heavy soiling, clean beforehand with a commercially available IPA cleaner (isopropyl alcohol 99,9 %). Never use cleaners that contain chlorine or citrus. Always clean with water and soap after cleaning with degreasing agent. After cleaning, wait at least half an hour until the surface has completely dried. Only then apply the product. A primer is recommended on concrete, wood and asphalt.
application	Before using the product, you should first use a test strip to check whether the floor is suitable for the product. Mark the place where the product is to be attached. Then remove approx. 10 cm of the protective film and press the material with the adhesive side firmly onto the floor. Unroll as much material as you need. Remove the protective film with one hand while pressing the material with your other hand. For a better adhesive result, we recommend a pressure roller in order to press the material evenly over the entire surface. Please do not glue the material overlapping.
usage	After attaching, the material is immediately accessible on foot, full usage is possible after 48 hours.
cleaning	The product can be cleaned with (warm) water and commercially available cleaning agents.

removing produkt	Start pulling the material off the floor at one corner. Heat facilitates removal; a temperature of 60° - 70° C is ideal. To remove adhesive residues, we recommend alcohol or a strong solvent. Test the compatibility on the floor beforehand.
warranty	The product products are conditionally warranted 2 years from purchase. Warranty claims are only limited to replacement of the product. The warranty does not cover the maneuvering of vehicles or items being dragged, pushed or scraped across such as pallets or transit skids.
Note	All technical data represent non-binding average values. Appropriate tests should decide on the usability. We reserve the right to make changes in the course of technical progress to improve the product.

DURABLE

Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77-79
D-58636 Iserlohn

Telefon +49 (0) 2371 / 662 – 0
Telefax +49 (0) 2371 / 662 – 221
Internet www.durable.de
E-Mail durable@durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

