



|  |                                    |
|--|------------------------------------|
| <b>Description:</b>                          | d-flexx Kilo barrier Ø 200x2000 mm |
| <b>Item number:</b>                          | DFKI+FU3                           |
| <b>GTIN:</b>                                 | 4250912395213                      |
| <b>Customs tariff number:</b>                | 39269097                           |
| <b>Material:</b>                             | Polyethylene                       |
| <b>Width (mm):</b>                           | 2004                               |
| <b>Height (mm):</b>                          | 1200                               |
| <b>Depth/Length (mm):</b>                    | 225                                |
| <b>Installation width (mm):</b>              | 2004                               |
| <b>Diameter (mm):</b>                        | 110/200                            |
| <b>Net weight (kg):</b>                      | 48,51                              |
| <b>Width without foot plate (mm):</b>        | 2004                               |
| <b>Depth without foot plate (mm):</b>        | 200                                |
| <b>Colour:</b>                               | yellow - black                     |
| <b>Foot plate width (mm):</b>                | 225                                |
| <b>Foot plate depth (mm):</b>                | 225                                |
| <b>Foot plate height (mm):</b>               | 10                                 |
| <b>Foot plate colour:</b>                    | black                              |
| <b>Area of application:</b>                  | indoor and outdoor use             |
| <b>Mounting location:</b>                    | paved ground                       |
| <b>Mounting:</b>                             | bolting                            |
| <b>Delivery is:</b>                          | pre-assembled                      |
| <b>Number of mounting holes:</b>             | 8                                  |
| <b>Fixing included:</b>                      | Concrete screw anchors M12 x 80 mm |
| <b>Tested to withstand force (Joule):</b>    | Top 2.500 J Bottom 10.000 J        |
| <b>Vehicle weight equivalent (kg):</b>       | 5.000 kg                           |
| <b>Vehicle equivalent speed (km/h):</b>      | 7,2 km/h                           |
| <b>Equivalent angle of impact:</b>           | 90°                                |
| <b>Deformation under maximal force (mm):</b> | 250                                |
| <b>Chemical Resistance:</b>                  | high-ISO/TR 10358                  |
| <b>Temperature Range:</b>                    | -40° up to +50°                    |
| <b>CO2 / m³:</b>                             | 18,5 kg                            |
| <b>Recyclability:</b>                        | 100%                               |
| <b>Warranty:</b>                             | 5 years                            |
| <b>Brand:</b>                                | d-flexx                            |
| <b>ETIM Class Code:</b>                      | EC004073                           |

